



KWR 250 01
Rechts



KWR 250 02
Links



Typ	ID	Verwendung für:	A mm	B mm	C mm	Gewicht kg
KWR 250 01	124065	ETA / ETA K 600 F, 600V, 600 H ACCU K 600 F	479	352	653	18,0
KWR 250 02	124066	ETA / ETA K 600 F, 600V, 600 H ACCU K 600 F	479	352	653	18,0

- Kaltwasserkühler
- Stahlblech, verzinkt
- Kondensatwanne
- Für Decken- und Wandmontage
- Anschluss NW 250
- Unisoliert

Lufteintritt t_{LE} (32°C 40% r.F.)

200 m³/h			300 m³/h			400 m³/h			500 m³/h			600 m³/h			700 m³/h		
t_{la} °C	Q kW	ΔP_{VL} Pa	t_{la} °C	Q kW	ΔP_{VL} Pa	t_{la} °C	Q kW	ΔP_{VL} Pa	t_{la} °C	Q kW	ΔP_{VL} Pa	t_{la} °C	Q kW	ΔP_{VL} Pa	t_{la} °C	Q kW	ΔP_{VL} Pa
14,8	1,6	10	16,2	2,2	14	16,8	2,8	20	17,5	3,3	35	18,1	3,8	52	18,7	4,3	68

Wasser t_{WE} (6 - 12 °C)

200 m³/h		300 m³/h		400 m³/h		500 m³/h		600 m³/h		700 m³/h	
ΔP_{KW} kPa	V_{KW} m³/h	ΔP_{KW} kPa	V_{KW} m³/h	ΔP_{KW} kPa	V_{KW} m³/h	ΔP_{KW} kPa	V_{KW} m³/h	ΔP_{KW} kPa	V_{KW} m³/h	ΔP_{KW} kPa	V_{KW} m³/h
1,3	0,3	2,3	0,3	3,5	0,4	4,8	0,49	6,1	0,56	7,5	0,6

Legende

- t_{la} = Luftaustrittstemperatur
 Q = Leistung Kühler
 ΔP_{VL} = Druckverlust Luft
 ΔP_{KW} = Druckverlust Wasser
 V_{KW} = Wassermenge

Zubehör:	Typ	ID
Dreiwegekugelhahn	STK 05	121620